

Color Variants

VG295150CA

Width 90 cm

Liquid gas 27,5 mbar

Included accessories

Optional accessories

WP400001

material

1 x WOK attachment ring.

Wok pan made of multiple-layer

VG295150CA Gas cooktop 200 series Width 90 cm

Liquid gas 27,5 mbar Wok burner with 5 KW

Control panel for comfortable and secure operation

Mechanical power level regulation for 9 power levels, with exact setting and reproduction of flame size

Multi-ring burner of solid, heat-resistant brass as used in professional kitchen Solid smooth-surface cast iron pan supports

Top appliance in the market, 17 kW on 5 burners

Cooking zones

1 multi-ring wok burner (300 W - 5000 W), suitable for pots up to max. ø 32

2 two-ring high output burners (170 W -4000 W), suitable for pots up to max. ø 28 cm.

2 two-ring standard burners (170 W -2000 W), suitable for pots up to max. ø 28 cm.

Handling

Control knobs with illuminated ring. Integrated control panel. One-handed operation. Electric ignition.

Features

Three-part cast iron pan support with flat, continuous pot surface. Brass burner rings.

Thermoelectric safety pilot. Residual heat indication. Operation indicator.

Planning notes

No intermediate shelf required. Appliance can be snapped into the worktop from above.

Rear panel and wall trims must be heat-resistant and consist of a nonflammable material.

Installation in a 90 cm wide lower cabinet is required.

A minimum lateral clearance of at least 11 13/16" from adjacent heat-sensitive furniture or contact surfaces must be observed or thermal insulation fitted. With a total connected load of more than 11 kW local regulations concerning room ventilation, room size and combination of extraction or recirculation hoods must be observed. Minimum clearance between gas cooktop(s) with more than 11 kW and ventilation hood 70 cm. Appliance weight: approx. 29.

Connection

Total connected load gas 17.0 KW. Total connected load electric 10.0 W. Connecting cable 1.5 m with plug.

Product Features

Product name / series name

gas hob w integrated controls

Construction type

Built-in

Energy source Gas

Total number of cooktop burners

Required cutout size (HxWxD) (mm) 106 x 885 x 492

Width of the appliance

914

Dimensions 106 x 914 x 510

Product packaging dimensions

(HxWxD) (mm)

290 x 700 x 1010

Net weight (kg)

28.879

Gross weight (kg)

31.2

Residual heat indicator

Location of control panel

Basic surface material

brushed stainless steel

Color of surface

Stainless steel Color of frame

Stainless steel

Approval certificates

CSA, CSA, CSA

Power cord length (cm)

Watts (W)

10 Gas connection rating (W)

17000

Current (A)

Volts (V) 110-120

Frequency (Hz)

50-60

Consumption and connection features


2021-02-25

Page 1



VG295150CA
Gas cooktop 200 series
Width 90 cm
Liquid gas 27,5 mbar
Wok burner with 5 KW

2021-02-25 Page 2



Minimum distance from the appliance out out to the side wall 11 (300 mm

Gas connection

