

FULGOR

MILANO

700 Series 30" Self Cleaning Double Wall Oven

F7DP30S1



Series

700

Type
Size
Colour
Stainless Steel Aesthetics
Oven Type
Temperature Regulation

PYRO
30"x30"
SS
Embossed window profile with bended edges
Multifunction 2 Fans (True Euro Convection)
Full Electronic

Key Functions

LIGHT	LIGHT		Upper/Lower
DEHIDR	DEFROST		Upper/Lower
	DEHYDRATE		Upper/Lower
KEEP WARM	WARM		Upper/Lower
	WARM +		Upper/Lower
BAKE	BAKE		Upper/Lower
	ROAST		Upper/Lower
	TRUE CONVECTION BAKE		Upper/Lower
CONV.	CONVECTION ROAST		Upper/Lower
	CONVECTION BAKE		Upper/Lower
	CONVECTION GRILL		Upper/Lower
	CONVECTION BROIL		Upper/Lower
PIZZA	PIZZA		Upper/Lower
BROIL	BROIL LEVELS		Upper/Lower
SELF C.	SELF CLEAN		Upper/Lower

Control Panel

Control type
Display
Menu Recipes

MODULAR - Electronic
TFT 3,5"

FULGOR

MILANO

Commands	Full Touch
Language	11
Special Features	
Demo Mode	•
Brightness setting (ON condition)	•
Brightness setting (OFF condition)	•
Beeper volume setting	•
Date format	•
Automatic Fast Preheat	•
Classic PIZZA function 310°C	•
Child Door Lock	•
Commands Lock	•
Sabbath mode	•
12/24 hours clock format	•
°C/°F degree unit	•
Door micro switch	•
Event logs (for Service)	•
Oven Door(s)	
Oven Glass Window	Large See Through Glass
Door Cooling System	4 Pane Heat Resistant Glass
Door Hinges	Heavy Duty Steady Tilt
Oven Cavity	
Gross Capacity (cbft)	4.4
Net Capacity (cbft)	4.1
Cavity Enameling Colour	Black
Rack Positions	6
Oven Lights	3 or 2 x 20W Halogen
Broil Upper Heating Element	3500 W (240V)
Upper Auxiliary Element Wattage	1032W (240V)
Concealed Bake Lower Heating Element	3000 W (240V)
Convection Element Wattage	2x1300W (240V)
Oven Accessories	
Chromed racks	•
Enameled Grill set (basin + anti splash)	•
Telescopic chromed rack	•
Meat probe	• Upper Oven Only
Dimensions/Weight - (In or Lbs)	
Overall dim - width	29 11/16" (754mm)
Overall dim - height	50 13/16" (1290mm)
Overall dim - depth	24" (610mm)
Cutout - width	28 7/16" (722mm)
Cutout - height (min)	50" (1270mm)
Cutout - depth (min)	23 1/4" (590mm)
Power / Ratings (208/240 V, 60 Hz)	
KW/Amps rating at 240V, 60Hz	7.50kW - 31.2A
KW/Amps rating at 208V, 60Hz	6.30kW - 30.3A
Cable + Conduit	•
INSTRUCTIONS FOR USE	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR